



EP4020

Extreme Protection



- Cold Start Protection • Smoother Running Engines
- Reduces Tappet Rattle and Smoke
- Extends the Life of the oil and Metal Components
- Heavy Duty Diff Protection and Temperature Drop
- Smoother Gear and Transmission Changes
- Lowers Oil Temperatures by reducing friction and drag
- Pure 100% Petroleum • Will not Void Warrantys

1 Litre • 5 Litres • 20 Litres • 205 Litres

EP4020



Directions for Engines:

Add **EP4020** at 5% of Engines crankcase quantity 2000 km before oil change. Change filter and oil and add another 5%.

After first 2 treatments, you only need to add to your oil changes every 15000 km. Trucks every 250 hrs.

Add **EP4020** to your 2 stroke oil at 5% than mix as directed to your petrol.

Directions for Drivetrain and Hydraulics:

Add **EP4020** at 5% to Drivetrain with a good clean quality oil. If oil is black it is contaminated and needs changing.

In large hydraulic systems >400 L you require 20 L **EP4020**.

Notes: The cleaning action of **EP4020** may lead to filter blockage after initial treatment - replace filters after 20 hrs of operation.

Flush and service automatic transmissions prior to adding **EP4020**.

Not compatible with brake fluid.

Safety Directions:

Avoid contact with skin. For advice, contact a Poisons Information Centre (Australia Ph. 13 11 26). This material and its container must be disposed of as hazardous waste. Avoid release to the environment.



Manufactured By: Smith Lubricants

A.B.N. 62 104 915 882 • 26 Hall Street • TEXAS QLD 4385

Phone 07 4653 1000 • www.SmithLubricants.com.au